

#### WWW.FLASHLIGHT.COM

# Engineering Data Sheet: 19101

### **Unit Information**

3 C-Cell Submersible Flashlight in orange- Alkaline

Model #: 19101

UPC-IC: 1673119101, Also available in rechargeable:

19111 (orange), 19112 (yellow), 19114 (black)

## **Master Pack Dimensions**

Weight: 7 lbs. 10 oz (3.46 kg)

Cube:  $1.03 \text{ ft}^3 (.03 \text{ m}^3)$ 

Cube Dimensions: 15.875" x 6.375" x 10.5"

Quantity: 12 pcs.

# **Specifications**

Power Source: 3 C Cell Bulb/Lamp: XPR3

Bulb/Lamp Life: 30 Hours

Light Output: 50,000 Beam Candlepower Weight (W/o batteries): 6.34 oz (.18 kg) Weight (w/ batteries) 16.3 oz (.46 kg) Replacement Bulb: XPR3 #21300 Burn Time (continuous) 5 hours

## **Components**

Lens Ring: Super-Tough Nylon w/ TPE

Lens: Polycarbonate
Reflector: Ultem 1000
Tube: Super-Tough Nylon
Contact Strip: Spring Steel
Lanyard: Braided Nylon (Black)
Belt Clip: Super-Tough Nylon

#### **Accessories Available**

595 Heavy Duty Leather Belt Holder SP-054/055 Slip-on wands (orange or yellow)

596 Velcro Belt Holster

19000 Charger Base

500202-N Ni-Cad Battery Pack

500170 120V AC Adapter 500180 12-24V DC Adapter

### **Unit Dimensions**

Length: 8.63 in. (21.92 cm) Width: 2.33 in. (5.91 cm) at head

Height: N/A



## **Safety Approvals**

UL: Class I, Division 1, Group D Operating Temp Code: T3A

UL & CSA: Class I, Division 2, Group A,B,C,D Class II, Division 2, Group G Operating Temp Code: T3

## **Product Features**

- Submersible to 100ft
- Non Conductive
- Limited Lifetime Warranty
- Passes 30 feet drop onto concrete
- Waterproof
- Pushbutton Switch
- Pre-focused spot beam
- 50,000 Candlepower, 5 hr continuous w/ alkaline batteries
- Key Ring, Lanyard, and Belt Clip Standard
- Self venting

**Product Comparison** 

1 Toduct Comparison				
Feature	KBS	UK	Pelican	Streamlight
Pre-focused spot beam	Yes	No	Yes	Yes
Submersible	Yes	No	Yes	Yes
Belt Clip	Yes	No	Yes	Yes
Standard flange base bulb	Yes	No	No	No
Super-Tough Nylon	Yes	No	No	No
Passes 30 foot drop test	Yes	No	Yes	No
Double Walled Tube	Yes	No	No	No