



WWW.FLASHLIGHT.COM

Engineering Data Sheet : 2206

Unit Information

5 6 Volt Waterproof Lantern
MModel #: 2206
UPC-IC (12 Digit): 01673070502

Unit Dimensions

Length: 8.2 in. (20.9 cm)
Width: 4.9 in. (12.4 cm)
Height: 5.6 in. (14.2 cm)

Master Pack Dimensions

Weight: 5.8 lbs. (2.6 kg)
Cube: 0.93 ft³ (0.02 m³)
Quantity: 6

Specifications

Power Source: Alkaline or Carbon Zinc 6V
Lantern Battery
Bulb/Lamp: KPR 113
Bulb/Lamp Life: 15 Hours
Light Output: 50,000 Beam Candlepower
Weight (Without batteries): 14.0 oz

Components

Lens Ring: Polypropylene (Black)
Lens: Unbreakable Tuflexx®
Reflector: Polycarbonate
Lantern Box: Polypropylene (Safety Orange)
Battery Connector: ABS Spring brass & tin coated steel
Switch: Rubber & co-polymer

Product Features

- For use in hazardous atmospheres
- Division 1 UL & CUL approved
- Waterproof & floating
- Krypton Bulb
- Alkaline Battery
- 200 yard light beam projection
- Switch guard protects switch on impacts
- Optional stand
- Spare bulb compartments
- Oversized reflector for more light output
- Glove size handle
- Circuit breaking mechanism



Safety Approvals

UL & CUL: Class I, Division 1, Group C & D
Class II, Division 1, Group G
Operating Temp T3B
CSA: Class I, Division 1, Group C & D
Class II, Division 1, Group G
Operating Temp T3A
ASTM & MSHA Approved

Accessories Available

2971 Battery Carousel, converts 4D batteries into a 6V spring terminal battery
22307 Wire Stand