



[WWW.FLASHLIGHT.COM](http://WWW.FLASHLIGHT.COM)

## Engineering Data Sheet : 2217

### Unit Information

2 D-Cell Waterproof Flashlight  
Model #: 2217  
UPC-IC (12 Digit): 01673144609

### Unit Dimensions

Length: 8.1 in. (20.6 cm)  
Width: 2.3 in. (5.8 cm) at head  
Height: N/A

### Master Pack Dimensions

Weight: 4.9 lbs. (2.2 kg)  
Cube: 0.39 ft<sup>3</sup> (0.01 m<sup>3</sup>)  
Quantity: 12

### Specifications

Power Source: Alkaline or Carbon Zinc: 2xD-cell  
Bulb/Lamp: PR-2  
Bulb/Lamp Life: 15 Hours  
Light Output: 10,000 Beam Candlepower  
Weight (Without batteries): 4.5 oz (.13 kg)

### Components

Lens Ring: Polypropylene  
Lense: Unbreakable Tuflexx®  
Reflector: ABS  
Tube: Polypropylene (Safety Orange)  
Contact Strip: Spring brass & tin coated steel  
Switch: Polypropylene  
Bottom Cap: Polypropylene (Black)  
Ring Hanger: ABS (Safety Orange)

### Product Features

- For use in hazardous atmospheres
- Division 1 UL & CUL approved
- Waterproof
- Spare bulb compartment
- Circuit breaking mechanism
- Ring Hanger
- Three-way switch : On-Off-Flash
- Anti-roll tube
- Oversized, faceted reflector for more light



**Model # 2217**

### Safety Approvals

UL & CUL: Class I, Division 1, Group C & D  
Class I, Division 2, Group A, B, C, & D  
Class II, Division 1, Group G  
Class III  
Operating Temp T3C  
CSA: Class I, Division 1, Group C & D  
Class II, Division 1, Group G  
Operating Temp T3C  
ASTM & MSHA Approved

### Accessories Available

SP-051 6-1/2" Red Snap In Wand  
SP-052 6-1/2" Yellow Snap In Wand  
SP-053 6-1/2" White Snap in Wand  
SP-054 Orange Slip on Wand  
595 Heavy Duty Leather Belt Holder  
596 Velcro Belt Holster