

SECTION 6 – REACTIVITY DATA

STABILITY: Stable

HAZARDOUS POLYMERIZATION: Will not occur

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition may yield carbon monoxide, carbon dioxide, and other hazardous products.

CONDITIONS TO AVOID: Heat, sparks, open flame, electrical equipment, fire, acids, caustics, etc.

INCOMPATIBILITY (MATERIALS TO AVOID): Acids, alkaline materials and oxidizers

SECTION 7 – SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all sources of ignition (heat, sparks, open flame). Avoid breathing vapors. Ventilate area. Contain and clean up spills with non-sparking tools, rags, etc. Use inert absorbent materials on small spills or Residuals of large spills.

WASTE DISPOSAL METHOD: Dispose of in accordance with local, state, and federal regulations.

SECTION 8 – SAFE HANDLING AND USE INFORMATION

RESPIRATORY PROTECTION: Provide NIOSH/MSHA approved organic vapor canister respirators where oxygen content is adequate and where Airborne mists and vapor concentrations are above the time-weighted threshold limit values. When using in poorly ventilated and confined spaces use a fresh air supply respirator or a self-contained breathing apparatus.

VENTILATION: Mechanical ventilation or local exhaust must be used to keep vapor concentrations below TLV. All ventilation equipment must be Explosion proof.

PROTECTIVE GLOVES: Impermeable chemical handling gloves for skin protection.

EYE PROTECTION: Use chemical safety glasses with side shields, goggles, and face shields

OTHER PROTECTIVE EQUIPMENT: Use impermeable aprons and protective clothing whenever possible to prevent skin contact. The use of Headcaps wherever possible is recommended.

HYGIENIC PRACTICES: Eye bath and safety shower recommended

SECTION 9 – SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Use non-sparking tools when handling this material. Avoid hot surfaces. Use in cool, well-ventilated areas. Keep containers closed when not in use. Keep away from excessive heat and open flames. Avoid prolonged or repeated contact with the skin. Normally accepted grounding techniques are to be employed during all phases of handling and application.

OTHER PRECAUTIONS: No smoking in areas where this material is used. Plastic utensils should not be used. Do not weld or flame cut on an "empty drum". Keep containers closed and upright when not in use. If the painted surface is to be welded, use a fan across the work area to prevent fumes from rising to the welder's face. Pump air into welder's hood to provide positive air pressure to prevent fumes from getting to welder. Maintain good personal hygiene and plant housekeeping.

This coating may contain materials classified as nuisance particulates which may be present at hazardous levels only during sanding or abrading of the dried film.

SECTION 10 – OTHER INFORMATION

SECTION 313 SUPPLIER NOTIFICATION: This product contains the following toxic chemicals subject to the reporting requirements of section 313 Of the Emergency planning and Community Right-To-Know Act of 1986 and of 40 CFR 372:

CHEMICAL NAME	CAS NUMBER	PCT BY WT
ZINC DUST	7440-66-6	39.55
ETHYL BENZENE	100-41-4	4.33
XYLOL	1330-20-7	32.64

DISCLAIMER OF LIABILITY

The information in this MSDS was obtained from sources we believe are reliable. HOWEVER, THE INFORMATION IS PROVIDED WITHOUT ANY REPRESENTATION OR WARRANTY, EXPRESSED OR IMPLIED, REGARDING ITS ACCURACY OR CORRECTNESS.

The conditions or methods of handling, storage, use, and disposal of the product are beyond our control and may be beyond our knowledge. FOR THIS AND OTHER REASONS, WE DO NOT ASSUME RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR LOSS, DAMAGE, OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH THE HANDLING, STORAGE, USE OR DISPOSAL OF THE PRODUCT.