

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Cartridges: EDOT22, EDOT56
Bulk Packaging: EDOT1KT, EDOT10KT, EDOT100KT, EDOTR
Product Description: General Purpose Epoxy-Based Anchoring Adhesive – Epoxy Resin
Company: Simpson Strong-Tie Company Inc.
Address: 5956 W. Las Positas Blvd.
Pleasanton, CA 94588 USA
Emergency Telephone Number: 1-800-535-5053 US/Canada
(24h) 1-352-323-3500 International
Date Prepared or Revised: December 2010
Supercedes: August 22, 2008
For most current MSDS, please visit our website at www.simpsonanchors.com.

2. COMPOSITION / INFORMATION ON INGREDIENTS

| Chemical Name | CAS Number | Concentration (Weight %) | OSHA Hazard |
|--|------------|--------------------------|-------------|
| BisPhenolA/Epichlorohydrin (Epoxy Resin) | 25068-38-6 | Proprietary | Yes |
| Talc | 14807-96-6 | Proprietary | Yes |
| Silica, amorphous (fumed) | 67762-90-7 | Proprietary | Yes |
| Titanium dioxide | 1317-80-2 | Proprietary | Yes |

Composition Note: The remaining ingredients are designated as “trade secret”.

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING! MAY CAUSE EYE AND/OR SKIN IRRITATION. PROLONGED OR REPEATED EXPOSURE MAY CAUSE SKIN SENSITIZATION.

POTENTIAL HEALTH EFFECTS**Acute**

Eye Contact: Exposure during handling may cause eye irritation, swelling, tearing, redness or cornea damage.

Skin Contact: Exposure during handling may cause moderate skin irritation. May cause skin sensitization, evidenced by rashes and hives.

Inhalation: Exposure to this product in excess of the applicable TVL or PEL may cause moderate irritation to the nose and respiratory tract. May cause Central Nervous System depression evidenced by headache, dizziness, and nausea.

Ingestion: Ingestion may cause irritation to the gastrointestinal tract. May cause Central Nervous System depression or other systemic effects.

Systemic Effects: Lungs, eyes, and skin.

Chronic:

Prolonged or repeated skin contact may cause a persistent irritation or dermatitis. Allergic reactions may arise in sensitive individuals.

Medical Conditions which May be Aggravated by Inhalation or Dermal Exposure:

Persons with eye, skin or respiratory disorders or unusual (hyper) sensitivity to chemicals may experience adverse reactions to this product.

4. FIRST AID MEASURES

Eye Contact: Immediately flush eyes with plenty of cool water for at least 15 minutes while holding the eyes open. If redness, burning, blurred vision, or swelling persists, **CONSULT A PHYSICIAN.**

Skin Contact: In case of contact, remove product and immediately wash affected area with plenty of soap and water for at least 5 minutes. Do not apply greases or ointments. Remove contaminated clothing. Clean contaminated clothing with soap and water before re-use. If redness, burning, or swelling persists, **CONSULT A PHYSICIAN.**

Ingestion: **DO NOT INDUCE VOMITING.** Never administer anything by mouth to an unconscious person. Rinse out mouth with water, then drink sips of water to remove taste from mouth. **CONSULT A PHYSICIAN.** Do not leave victim unattended. If vomiting occurs spontaneously, lay victim on the side and keep head lower than waist to prevent aspiration.

Inhalation: If respiratory irritation or distress occurs, remove victim to fresh air. If breathing is difficult, give oxygen. If breathing stop, apply artificial respiration. **CONSULT A PHYSICIAN.**

Notes to Physician: All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media: Water fog, carbon dioxide or dry chemical, aqueous foam.

Fire And Explosion Hazards: Hazardous gases/vapors produced are carbon monoxide, carbon dioxide, and aldehydes and miscellaneous hydrocarbons. Do not allow run-off from fire fighting to enter drains or water courses.

Fire Fighting Equipment and Procedures: Wear full protective clothing and self-contained breathing apparatus for fire fighting. Isolate fuel supply from fire. Use water spray to cool fire-exposed surfaces and containers.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: Use cautious judgment when cleaning up spill. Shut off leaks, if possible without personal risk. Wear suitable protective clothing, gloves and eye/face protection. Evacuate personnel to safe areas.

Environmental Precautions: Construct a dike to prevent spreading. Keep out of sewers, storm drains, surface waters, and soils.

Clean-up Methods: **Small spills:** Soak up with absorbent material such as clay, sand or other suitable non-reactive material. Place in leak-proof containers. Seal tightly for proper disposal. **Large spills:** Approach suspected leak areas with caution. Create a dike or trench to contain material. Soak up with absorbent material such as clay, sand or other suitable non-reactive material. Place in leak-proof containers. Seal tightly for proper disposal.

Additional Information: Notify authorities if any exposures to the general public or environment occur or are likely to occur. Dispose in accordance with federal, state, and local regulations.

7. HANDLING AND STORAGE

Handling (Personnel): To prevent skin and eyes contact under the foreseeable conditions of use, wear appropriate protective clothing and safety eyewear. When handling, do not eat, drink, or smoke. Wash thoroughly after handling. Avoid breathing fumes. Handle in a well-ventilated work area.

Handling (Physical Aspects): Close container after each use. Keep away from heat, sparks and flames.

Storage: Keep away from: acids, oxidizing agents, heat, or flames. Store in a cool, dry, well-ventilated area in closed containers. Protect containers from physical damage.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits:

| Chemical Name | ACGIH (TLV) | OSHA (PEL) |
|--|----------------------|----------------------|
| BisPhenolA/Epichlorohydrin (Epoxy Resin) | N/E | N/E |
| Talc (respirable ⁽¹⁾) | 2 mg/m ³ | 5 mg/m ³ |
| Silica, amorphous inhalable | 6 mg/m ³ | 10 mg/m ³ |
| Titanium dioxide (total dust) | 10 mg/m ³ | 10 mg/m ³ |

⁽¹⁾ This component poses a hazard only if the liquid product dries and a dust is formed.

EDOT™ General Purpose Epoxy-Tie® Anchoring Adhesive - MATERIAL SAFETY DATA SHEET

| | |
|--------------------------------|--|
| Engineering Controls: | Where engineering controls are indicated by use conditions or a potential for excessive exposure exists, the following traditional exposure techniques may be used to effectively minimize employee exposures. |
| Eye Protection: | When engaged in activities where product could contact the eye, wear safety glasses with side shields, chemical splash goggles, or face shield. |
| Skin Protection: | Skin contact should be minimized through use of Nitrile, neoprene or butyl gloves and suitable long sleeved clothing. Consideration must be given both to durability as well as permeation resistance. |
| Respirator Protection: | Avoid actions that cause dust exposure to occur. Use local or general ventilation to control exposures below applicable exposure limits. NIOSH or MSHA approved particulate filter respirators should be used to control exposures when ventilation or other controls are inadequate or discomfort or irritation is experienced. Respirator and/or filter cartridge selection should be based on American National Standards Institute (ANSI) Standards Z88.2 - Practices for Respiratory Protection. |
| Ventilation: | Use local exhaust or general dilution ventilation to control exposure within applicable limits. |
| Work Practice Controls: | Personal hygiene is an important work practice exposure control measure and the following general measures should be taken when working with or handling this material: <ol style="list-style-type: none"> (1) Do not store, use, and/or consume foods, beverages, tobacco products, or cosmetics in areas where this material is stored. (2) Wash hands and face carefully before eating, drinking, using tobacco, applying cosmetics, or using the toilet. Wash exposed skin promptly to remove accidental splashes or contact with this material. |

9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|-----------------------------|----------------------------|
| Form: | Paste |
| Color: | White |
| Odor: | Mild |
| Vapor Pressure: | Not Volatile |
| Boiling Point: | N/E |
| Freezing Point: | N/E |
| Flash Point: | 288°F (142°C) (Closed cup) |
| Specific Gravity: | 1.52@ 72°F |
| pH: | 8.8 |
| Solubility In Water: | Insoluble |

10. STABILITY AND REACTIVITY

| | |
|--|--|
| Stability: | Stable under normal conditions. |
| Conditions To Avoid: | Incompatible chemicals, heat and open flame. |
| Materials To Avoid: | Oxidizing and reducing agents. |
| Hazardous Decomposition Products: | Combustion may produce carbon monoxide, carbon dioxide, aldehydes, miscellaneous hydrocarbons, and other organic substances. |
| Hazardous Polymerization: | Will not occur. |

11. TOXICOLOGICAL INFORMATION

| | |
|---|---|
| Acute Toxicity: | |
| Oral (LD₅₀, Rat): | N/E |
| Dermal (LD₅₀, Rabbit): | N/E |
| Inhalation (LC₅₀, Rat): | N/E |
| Chronic Health Hazard: | No known significant effects or critical hazards. Repeated or prolonged exposure may cause allergic skin reaction and/or limited sensitization. |
| Carcinogenic Classification: | IARC <u>Yes*</u> ; ACGIH <u>No</u> ; NTP <u>No</u> ; OSHA <u>No</u> . |
| | * This product contains trace amounts of substances listed as carcinogens under IARC's guidelines (Group 2b). |

12. ECOLOGICAL INFORMATION

Ecotoxicity: This product has not been evaluated.
Chemical Fate Information: No data found for product.

13. DISPOSAL CONSIDERATIONS

Waste Disposal: This material is not a hazardous waste by RCRA criteria (40CFR 261). Dispose of container and unused contents in accordance to local, state and federal regulations.
Container Disposal Method: Emptied container may contain product residue and should not be reused.

14. TRANSPORTATION INFORMATION

DOT/TDG: Not Regulated For Transport.
IATA: Not Regulated For Transport.
IMO: Not Regulated For Transport.

15. REGULATORY INFORMATION**US FEDERAL REGULATIONS:****OSHA Hazard Communication Standard (29CFR 1910.1200):**

This product is considered a "hazardous chemical" under this regulation.

Status Under Toxic Substances Control Act (TSCA) (40 CFR 710):

All chemical(s) comprising this product are either exempt or listed on the TSCA Inventory.

EPA Reportable Quantities:

Clean Water Act (40CFR Section 112): None required.

CERCLA Hazardous Substance (40CFR Part 302, Table 302.4): None required.

EPCRA Extreme Hazardous Substance (40CFR Section 302 Part 355): None required.

Toxic Chemical Release Inventory (TRI) Reporting - (SARA Title III Section 313 (40 CFR 372) Component(s) above 'de minimus' level): None required.

SARA Title III Hazard Classes (40CFR 370 Sections 311 and 312):

Fire Hazard: No
Reactive Hazard: No
Release of Pressure: No
Acute Health Hazard: Yes
Chronic Health Hazard: Yes

US STATE REGULATIONS:**California - "Safe Drinking Water and Toxic Enforcement Act" (Proposition 65):**

This product contains chemicals that are known to the State of California to cause cancer and/or reproductive toxicity and other harm.

| Component | Concentration | Remarks |
|----------------------|---------------|--------------|
| Phenylglycidyl ether | <3 ppm | Carcinogenic |
| Epichlorohydrin | <1 ppm | Carcinogenic |

INTERNATIONAL REGULATIONS:**CANADIAN DSL/NDSL INVENTORY STATUS:**

Components of this product are listed on the Canadian DSL or NDSL inventories.

CANADIAN WHMIS CLASSIFICATION and SYMBOLS:

Class D-2B: Material causing other toxic effects




16. OTHER INFORMATION

HAZARD RATINGS:

Hazardous Material Information System (HMIS)

| | |
|---------------------|---|
| Health | 2 |
| Flammability | 1 |
| Physical Hazard | 0 |
| Personal Protection | B |

National Fire Protection Association (NFPA)



HMIS/NFPA Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme
Protective Equipment: Safety glasses, gloves

This Material Safety Data Sheet (MSDS) is prepared by Simpson Strong-Tie Company Inc. in compliance with the requirements of OSHA 29 CFR Part 1910.1200. The information it contains is offered in good faith as accurate as of the date of this MSDS. This MSDS is provided solely for the purpose of conveying health, safety, and environmental information. No warranty, expressed or implied, is given. Health and Safety precautions may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations.

© Copyright 2010 Simpson Strong-Tie Company Inc.

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Cartridges: EDOT22, EDOT56
 Bulk Packaging: EDOT1KT, EDOT10KT, EDOT100KT, EDOTH
Product Description: General Purpose Epoxy-Based Anchoring Adhesive - Epoxy Hardener
Company: Simpson Strong-Tie Company Inc.
Address: 5956 W. Las Positas Blvd.
 Pleasanton, CA 94588 USA
Emergency Telephone Number: 1-800-535-5053 US/Canada
 (24h) 1-352-323-3500 International
Date Prepared or Revised: December 2010
Supercedes: August 22, 2008
 For most current MSDS, please visit our website at www.simpsonanchors.com.

2. COMPOSITION / INFORMATION ON INGREDIENTS

| Chemical Name | CAS Number | Concentration (Weight %) | OSHA Hazard |
|---------------------------|------------|--------------------------|-------------|
| Aliphatic amines | N/E | Proprietary | Yes |
| Silica, amorphous (fumed) | 67762-90-7 | Proprietary | Yes |
| Talc | 14807-96-6 | Proprietary | Yes |

Composition Note: The remaining ingredients are designated as “trade secret”.

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING! CORROSIVE. SEVERE IRRITATION TO EYES AND SKIN. PROLONGED OR REPEATED EXPOSURE MAY CAUSE SKIN SENSITIZATION. COMPONENTS OF THE PRODUCT MAY AFFECT THE NERVOUS SYSTEM.

POTENTIAL HEALTH EFFECTS

Acute

Eye Contact: Exposure during handling may cause severe eye irritation, swelling, tearing, redness or cornea damage.
Skin Contact: Exposure during handling may cause severe skin irritation. May cause skin sensitization, evidenced by rashes and hives.
Inhalation: Exposure to this product in excess of the applicable TVL or PEL may cause moderate irritation to the nose and respiratory tract. May cause Central Nervous System depression evidenced by headache, dizziness, and nausea.
Ingestion: Ingestion may cause irritation to the gastrointestinal tract. May cause Central Nervous System depression or other systemic effects.
Systemic Effects: Lungs, eyes, and skin.

Chronic:

Prolonged or repeated skin contact may cause a persistent irritation or dermatitis. Allergic reactions may arise in sensitive individuals.

Medical Conditions which May be Aggravated by Inhalation or Dermal Exposure:

Persons with eye, skin or respiratory disorders or unusual (hyper) sensitivity to chemicals may experience adverse reactions to this product.

4. FIRST AID MEASURES

Eye Contact: Immediately flush eyes with plenty of cool water for at least 15 minutes while holding the eyes open. If redness, burning, blurred vision, or swelling persists, **CONSULT A PHYSICIAN.**
Skin Contact: In case of contact, remove product and immediately wash affected area with plenty of soap and water for at least 5 minutes. Do not apply greases or ointments. Remove

Ingestion: contaminated clothing. Clean contaminated clothing with soap and water before re-use. If redness, burning, or swelling persists, **CONSULT A PHYSICIAN.**
DO NOT INDUCE VOMITING. Never administer anything by mouth to an unconscious person. Rinse out mouth with water, then drink sips of water to remove taste from mouth. **CONSULT A PHYSICIAN.** Do not leave victim unattended. If vomiting occurs spontaneously, lay victim on side and keep head lower than waist to prevent aspiration.

Inhalation: If respiratory irritation or distress occurs, remove victim to fresh air. If breathing is difficult, give oxygen. If breathing stop, apply artificial respiration. **CONSULT A PHYSICIAN.**

Notes to Physician: All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media: Water fog, carbon dioxide or dry chemical, aqueous foam.

Fire And Explosion Hazard: Irritating and toxic fumes may be produced at high temperature. Hazardous gases/vapors produced are carbon monoxide, carbon dioxide, oxides of nitrogen, cyanide, and miscellaneous hydrocarbons. Do not allow run-off from fire fighting to enter drains or water courses.

Fire Fighting Equipment and Procedures: Wear full protective clothing and self-contained breathing apparatus for fire fighting. Isolate fuel supply from fire. Use water spray to cool fire-exposed surfaces and containers.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: Use cautious judgment when cleaning up spill. Shut off leaks, if possible without personal risk. Wear suitable protective clothing, gloves and eye/face protection. Evacuate personnel to safe areas.

Environmental Precautions: Construct a dike to prevent spreading. Keep out of sewers, storm drains, surface waters, and soils.

Clean-up Methods: **Small spills:** Soak up with absorbent material such as clay, sand or other suitable non-reactive material. Place in leak-proof containers. Seal tightly for proper disposal. **Large spills:** Approach suspected leak areas with caution. Create a dike or trench to contain material. Soak up with absorbent material such as clay, sand or other suitable non-reactive material. Place in leak-proof containers. Seal tightly for proper disposal.

Additional Information: Notify authorities if any exposures to the general public or environment occur or are likely to occur. Dispose in accordance with federal, state, and local regulations.

7. HANDLING AND STORAGE

Handling (Personnel): To prevent skin and eyes contact under the foreseeable conditions of use, wear appropriate protective clothing and safety eyewear. When handling, do not eat, drink, or smoke. Wash thoroughly after handling. Avoid breathing fumes. Handle in a well-ventilated work area.

Handling (Physical Aspects): Close container after each use. Keep away from heat, sparks and flames.

Storage: Keep away from: acids, oxidizers, heat, or flames. Store in a cool, dry, well-ventilated area in closed containers. Protect containers from physical damage.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits:

| Chemical Name | ACGIH (TLV) | OSHA (PEL) |
|--------------------------------------|---------------------|----------------------|
| Aliphatic amines | N/E | N/E |
| Silica, amorphous (fumed), inhalable | 6 mg/m ³ | 10 mg/m ³ |
| Talc (respirable ⁽¹⁾) | 2 mg/m ³ | 5 mg/m ³ |

⁽¹⁾This component poses a hazard only if the liquid product dries and a dust is formed.

EDOT™ General Purpose Epoxy-Tie® Anchoring Adhesive - MATERIAL SAFETY DATA SHEET

| | |
|--------------------------------|--|
| Engineering Controls: | Where engineering controls are indicated by use conditions or a potential for excessive exposure exists, the following traditional exposure techniques may be used to effectively minimize employee exposures. |
| Eye Protection: | When engaged in activities where product could contact the eye, wear safety glasses with side shields, chemical splash goggles, or face shield. |
| Skin Protection: | Skin contact should be minimized through use of Nitrile, neoprene or butyl gloves and suitable long sleeved clothing. Consideration must be given both to durability as well as permeation resistance. |
| Respirator Protection: | Avoid actions that cause dust exposure to occur. Use local or general ventilation to control exposures below applicable exposure limits. NIOSH or MSHA approved particulate filter respirators should be used to control exposures when ventilation or other controls are inadequate or discomfort or irritation is experienced. Respirator and/or filter cartridge selection should be based on American National Standards Institute (ANSI) Standards Z88.2 - Practices for Respiratory Protection. |
| Ventilation: | Use local exhaust or general dilution ventilation to control exposure within applicable limits. |
| Work Practice Controls: | Personal hygiene is an important work practice exposure control measure and the following general measures should be taken when working with or handling this material: <ol style="list-style-type: none"> (1) Do not store, use, and/or consume foods, beverages, tobacco products, or cosmetics in areas where this material is stored. (2) Wash hands and face carefully before eating, drinking, using tobacco, applying cosmetics, or using the toilet. Wash exposed skin promptly to remove accidental splashes or contact with this material. |

9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|-----------------------------|----------------------------|
| Form: | Paste |
| Color: | Brown |
| Odor: | Ammonia/Aromatic |
| Boiling Point: | N/E |
| Freezing Point: | N/E |
| Vapor Pressure: | N/E |
| Flash Point: | 255°F (124°C) (Closed cup) |
| Specific Gravity: | 1.59@ 72°F |
| pH: | 10.7 |
| Solubility In Water: | Slight |

10. STABILITY AND REACTIVITY

| | |
|--|---|
| Stability: | Stable under normal storage conditions. |
| Conditions To Avoid: | Incompatible chemicals, high heat, and open flame. |
| Materials To Avoid: | Avoid contact with oxidizing agents and acids. |
| Hazardous Decomposition Products: | Combustion may produce carbon monoxide, carbon dioxide, nitrogen oxide, miscellaneous hydrocarbons, and other organic substances. |
| Hazardous Polymerization: | Will not occur. |

11. TOXICOLOGICAL INFORMATION

| | |
|---|--|
| Acute Toxicity: | |
| Oral (LD₅₀, Rat): | N/E |
| Dermal (LD₅₀, Rabbit): | N/E |
| Inhalation (LC₅₀, Rat): | N/E |
| Chronic Health Hazard: | Repeated or prolonged exposure may cause allergic skin reaction and/or limited sensitization. |
| Carcinogenic Classification: | IARC <u>Yes*</u> ; ACGIH <u>No</u> ; NTP <u>Yes*</u> ; OSHA <u>No</u> . |
| | * This product contains trace amounts of substances listed as carcinogens under the guidelines of IARC(Group 1) and NTP. |

12. ECOLOGICAL INFORMATION

Ecotoxicity: This product has not been evaluated.
Chemical Fate Information: No data found for product.

13. DISPOSAL CONSIDERATIONS

Waste Disposal: Dispose of container and unused contents in accordance to local, state and federal regulations.
Container Disposal Method: Emptied container may contain product residue and should not be reused.

14. TRANSPORTATION INFORMATION

DOT/TDG: Cartridges: ORM-D / Limited Quantity
Bulk Packaging:
UN Number: UN2735
Proper Shipping Name: Amines, Liquid, Corrosive, n.o.s. (Diethylenetriamine)
Hazard Class: 8
Packing Group: II



Hazard Label:

IATA: UN Number: UN2735
Proper Shipping Name: Amines, Liquid, Corrosive, n.o.s. (Diethylenetriamine)
Hazard Class: 8
Packing Group: II



Hazard Label:

IMO: Cartridges: Limited Quantity
Bulk Packaging:
UN Number: UN2735
Proper Shipping Name: Amines, Liquid, Corrosive, n.o.s. (Diethylenetriamine)
Hazard Class: 8
Packing Group: II



Hazard Label:

15. REGULATORY INFORMATION**US FEDERAL REGULATIONS:****OSHA Hazard Communication Standard (29CFR 1910.1200):**

This product is considered a "hazardous chemical" under this regulation.

Status Under Toxic Substances Control Act (TSCA) (40 CFR 710):

All chemical(s) comprising this product are either exempt or listed on the TSCA Inventory.

EPA Reportable Quantities:

Clean Water Act (40CFR Section 112): None required.

CERCLA Hazardous Substance (40CFR Part 302, Table 302.4): None required.

EPCRA Extreme Hazardous Substance (40CFR Section 302 Part 355): None required.

Toxic Chemical Release Inventory (TRI) Reporting - (SARA Title III Section 313 (40 CFR 372) Component(s) above 'de minimus' level): None required

SARA Title III Hazard Classes (40CFR 370 Sections 311 and 312):

| | |
|-------------------------------|-----|
| Fire Hazard: | No |
| Reactive Hazard: | No |
| Release of Pressure: | No |
| Acute Health Hazard: | Yes |
| Chronic Health Hazard: | Yes |

US STATE REGULATIONS:

California - "Safe Drinking Water and Toxic Enforcement Act" (Proposition 65):

This product contains chemicals that are known to the State of California to cause cancer and/or reproductive toxicity and other harm.

| Component | % In Blend (approx.) | Remark |
|---------------------------------|----------------------|--------------|
| Crystalline Silica (Respirable) | Trace | Carcinogenic |

INTERNATIONAL REGULATIONS:

CANADIAN DSL/ NDSL INVENTORY STATUS:

Components of this product are listed on the Canadian DSL or NDSL inventories.

CANADIAN WHMIS CLASSIFICATION and SYMBOLS:

Class E: Corrosive



Class D-2B: Material causing other toxic effects




16. OTHER INFORMATION

HAZARD RATINGS:

Hazardous Material Information System (HMIS)

| | |
|---------------------|---|
| Health | 3 |
| Flammability | 1 |
| Physical Hazard | 0 |
| Personal Protection | B |

National Fire Protection Association (NFPA)



HMIS/NFPA Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme

Protective Equipment: Safety glasses, gloves

This Material Safety Data Sheet (MSDS) is prepared by Simpson Strong-Tie Company Inc. in compliance with the requirements of OSHA 29 CFR Part 1910.1200. The information it contains is offered in good faith as accurate as of the date of this MSDS. This MSDS is provided solely for the purpose of conveying health, safety, and environmental information. No warranty, expressed or implied, is given. Health and Safety precautions may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations.

© Copyright 2010 Simpson Strong-Tie Company Inc.